

Epoca's design is based on an extremely dynamic, informal style.

The semi-automatic **Epoca S** version is extremely easy to use and reliable in every situation.

Available in versions with 1 group, 1 group TANK and 2 groups.



The filter holder is fitted with a new ergonomic handle, designed to ensure smooth wrist movement and maximum user comfort.



The EPOCA range of features is rounded off by side-mounted shockproof bumpers, offering ample protection even at the busiest times of day.



Red and coal grey are enhanced by a metallic effect that gives Epoca a shiny, modern feel.



EPOCA's great flexibility is seen to the full in the Tank S version, thanks to the use of an independent water tank that makes it versatile and usable even in locations without access to a water supply.





Epoca S - 2 groups - front view



Epoca S - 2 groups - rear view



Epoca S - 2 groups - side view













EPOCA S/S-TANK



Technical Features

independent heat exchangers
electric heating
incorporated volumetric pump
boiler pressure gauge
automatic water level control

Standard features, accessories

STANDARD FEATURES: 1 filter holder for 2 cups per group, 1 filter holder for 1 cup, 2 steam wands for version with 2 groups, 1 steam wand for version with 1 group, 1 hot water dispenser, coffee tamper, blind filter and measuring scoop.

ACCESSORIES: DP automatic or manual water softener, MD dosing grinder.

Materials

housing in stainless steel, base and sides in HDPE and ABS

Colors

metallic red and metallic grey.

Technical Data

1 GROUP

dimensions (W×0×H) 15.2×22.0×18.9 in (385×560×480	mm) weight	boiler (29 kg) 41 (0.9 ga	
boiler power	voltage	frequency	frequency
1,600 W (120 V) - 1,700 W	120 V / 220-240 V	50/60 Hz) Hz

1 GROUP - TANK

dimensions (W×D×H) 15.2×22.0×18.9 in (385×560×480 mm)	water tank 21 (0.45 gal _{uk})	weight 61.7 lb (28 kg)	boiler 41 (0.9 gal _{ux})
boiler power	voltage		frequency
1,600 W (120 V) - 1,700 W	120 V / 220-240 V		50/60 Hz

2 GROUPS

dimensions (W×0×H) weig		reight	boiler
30.7×22.0×18.9 in (780×560×480 mm)		9.11b (54 kg)	11 I (2.4 gal _{uk})
boiler power	voltage 120 V / 220-240 V / 380-415 V (3N)		frequency
3,200 W (120 V) - 4,300 W			50/60 Hz

Standard







On demand









(*) not available for 1 group version



Aishwarya Consolidates Pvt. Ltd.,

#19, Frist Floor, 10th 'B' Main, 27th Cross, Third Block Jayanagar, BANGALORE – 560 011, INDIA Tel: +91-80-2664 1200/1/2 Fax: +91-80-2664 1204

E-mail : aishtek@vsnl.com www.aishwaryaconsolidates.com