



**Model: BC With Sliding Doors  
BC2 & BC3**

Project: .....

Location: .....

Item #: .....

Quantity: .....

<i>Variant</i>	<i>Op Temp &amp; Storage</i>
BC2 With Sliding Doors	+4/+10°C - General Produce
BC3 With Sliding Doors	+4/+10°C - General Produce

**Key Features**

- Tough and durable stainless steel exterior and interior
- Excellent anti-condensation lockable self closing double glazed Argon gas doors with easy to clean and replace magnetic balloon gasket
- 75mm environmentally friendly ODP (Ozone Depletion Potential) Zero foam insulation for excellent thermal efficiency and performance
- Lock to all doors
- Adjustable PE coated shelves for effective storage and display of varying sized bottles and cans, accommodate vertical stacking capacity of three levels of 10" bottle
- Adjustable front leveling feet
- Waste heat recovery vaporizer
- Automatic re-evaporation
- CFC free R130a refrigerants
- Design for efficient and effective operation in 32°C ambient environments
- Technically advanced forced air refrigeration system for efficient and effective performance
- Individual on/off switch for interior light
- HACCP Complaint



## Dimension

	BC2 With Sliding Doors	BC3 With Sliding Doors
<b>External (mm):</b>	H895 W900 D530	H895 W1352 D530
<b>Internal (mm): (width per section)</b>	H745 W830 D378	H745 W1282 D378
<b>Packed (max):</b>	H910 W930 D560	H910 W1362 D560
<b>Weight: Add 5kg per product for packing</b>	80kg	110kg

## Important Information

	BC2 With Sliding Doors	BC3 With Sliding Doors
<b>Capacity:</b> 330ml bottles	182	278
<b>Construction:</b> Exterior Interior Door	0.7mm 430 0.7mm 304 BA stainless steel frame 1.2 mm 430 S/S frame with double glazed glass	0.7mm 430 0.7mm 304 BA stainless steel frame 1.2 mm 430 S/S frame with double glazed glass
<b>Power Supply:</b>	220V/240V 50Hz/1Ph 13 amp plug	220V/240V 50Hz/1Ph 13 amp plug
<b>Power Input:</b> Start Up Running Compressor HP	12 amps 2.0 amps 1/5	12 amps 2.4 amps 1/4
<b>Refrigerant::</b>	R134a	R134a
<b>Defrost:</b>	Automatic defrost and evaporation	Automatic defrost and evaporation
<b>Insulation (max):</b> ODP Zero Polyurethane	35mm	35mm
<b>Fittings:</b> Shelves	2 shelves	6 shelves

All refrigeration equipment require adequate ventilation for efficient and effective performance.

Williams are committed to a policy continuing product development and innovation and as such, we reserve the right to change product specifications stated without prior notice.



V12008 JW/07/06



**Aishwarya Consolidates Pvt. Ltd.,**  
 #19, Frist Floor, 10<sup>th</sup> 'B' Main, 27<sup>th</sup> Cross,  
 Third Block Jayanagar, BANGALORE – 560 011, INDIA  
 Tel: +91-80-2664 1200/1/2 Fax: +91-80-2664 1204  
 E-mail : [aishtek@vsnl.com](mailto:aishtek@vsnl.com) [www.aishwaryaconsolidates.com](http://www.aishwaryaconsolidates.com)