



Model: *Bottle Coolers* *BC1/BC2/BC3*

Optional Features

- Stainless steel exterior
- Stainless steel solid doors

Variant	Op Temp & Storage
BC1	+4/+10°C
BC2	+4/+10°C
BC3	+4/+10°C

Key Features

- Range of models to suit your capacity requirements
- Flexible operating temperatures from 4°C/10°C
- Choice of finishes – black PVC coated galvanized steel or 430 stainless steel
- Hard wearing exterior with hygienic, easy to clean mirrored stainless steel interior
- Double glazed doors and bright, low energy consumption lighting for excellent display and presentation
- Self-closing, lockable doors fitted with easy to clean and replace magnetic balloon gaskets
- Designed for effective and efficient refrigerated storage and display of chilled bottled and canned drinks in 32°C ambient environments
- Easy to adjust thermostat
- Fully adjustable nylon coated wire shelves to suit stacking requirements and accommodate vertical stacking capacity of three levels of 10" bottles
- Adjustable leveling feet ensures counter stability in any environment
- Environmentally friendly 75 mm ODP Zero polyurethane foam injected insulation for excellent energy efficiency and performance
- Designed and built to ISO9001-2000 Quality Management Standards



Dimensions

	BC1	BC2	BC3
External (mm):	H895 W600 D530	H895 W900 D530	H895 W1352 D530
Internal (mm):	H745 W520 D378 D253	H745 W830 D378 D253	H745 W1282 D378 D253
Door Opening (mm):	D1130	D1130	D1130
Packed (mm):	H995 W700 D630	H995 W1000 D630	H995 W1450 D630
Weight: Add 5kg per product for packing	57kg	57kg	65kg

Important Information

	BC1	BC2	BC3
Capacity: 330ml bottles	112	182	278
Construction:			
Exterior	0.7 430 stainless steel or PVC coated galvanised steel	0.7 430 stainless steel or PVC coated galvanised steel	0.7 430 stainless steel or PVC coated galvanised steel
Interior	0.7 430 BA mirrored stainless steel	0.7 430 BA mirrored stainless steel	0.7 430 BA mirrored stainless steel
Door	Double glassed with brushed aluminium surround	Double glassed with brushed aluminium surround	Double glassed with brushed aluminium surround
Power Supply:	220V/240V 50Hz/1Ph 13 amp plug	220V/240V 50Hz/1Ph 13 amp plug	220V/240V 50Hz/1Ph 13 amp plug
Power Input:			
Start Up	9 amps	9 amps	9 amps
Running	1.75 amps	2 amps	2.4 amps
Compress HP	1/5	1/5	1/5
Energy Consumption:	2.8kW in 24hr	3.2kW in 24hr	6.8kW in 24hr
Heat Rejection: Evaporating at -10°C in 32°C ambient)	369 watts	369 watts	507 watts
Refrigerant::	R134a	R134a	R134a
Defrost:	Automatic defrost and evaporation	Automatic defrost and evaporation	Automatic defrost and evaporation
Insulation (max): ODP Zero Polyurethane	75mm	75mm	75mm
Noise Output:	dBA	dBA	dBA
Fittings: Shelves (Nylon coated wire)	2	4	6

Solid doors are shipped with no lights – please request lights at time of order if required or replacement to glass doors planned in future.

All refrigeration equipment require adequate ventilation for efficient and effective performance.

Williams are committed to a policy continuing product development and innovation and as such, we reserve the right to change product specifications stated without prior notice.



V12006 – JW/5/06



Aishwarya Consolidates Pvt. Ltd.,
 #19, Frist Floor, 10th 'B' Main, 27th Cross,
 Third Block Jayanagar, BANGALORE – 560 011, INDIA
 Tel: +91-80-2664 1200/1/2 Fax: +91-80-2664 1204
 E-mail : aishtek@vsnl.com www.aishwaryaconsolidates.com