



## Model: Onyx CPC Range

Variant	Op Temp & Storage
CPC3	+1/+4°C
CPC4	+1/+4°C
CPC5	+1/+4°C

### Optional Features

- Bank of 2 drawers
- Hinged cover
- Granite worktop / Polypropylene worktop
- 1/3 x 150 Gastronorm pans with lids
- Stainless steel back

### Key Features

- 430 stainless steel exterior and 304 stainless steel interior finish for hygiene and durability
- CoolSmart intelligent controller offering 15% energy savings, enhanced performance; energy efficient economy mode ensuring effective temperature control for excellent food safety and improved defrost functionality for increased cabinet efficiency
- CoolSmart controller is designed for easy operation and features clear digital display
- High performance, efficient commercial refrigeration system for increased energy efficiency and quieter improved performance
- Efficient and effective performance in 43°C ambient environments
- Unique air flow design with protective 1°C air curtain ensures food temperature in pans is maintained at 4°C
- Accommodates either 7, 10 or 12 1/3GN containers in raised panholder and 1/1 shelves or containers behind the doors
- Removable, easy clean crumb tray and lift off night cover
- 75mm environmentally friendly ODP zero foam insulation for excellent thermal efficiency
- Self closing lockable doors with 90° dwell and fitted with easy to clean and replace magnetic balloon gaskets
- 128mm heavy duty, non marking front and rear swivel and break castors for easy positioning and maneuverability
- Removable internal fittings including racking and shelf supports for easy cleaning and hygiene
- Designed and built to ISO9001-2000 Quality Management Standards
- HACCP compliant



### Dimensions

<b>External (mm):</b>	H1100 max H865 counter W1470 D850 D385 counter	H1100 max H865 counter W1935 D850 D385 counter	H1100 max H865 counter W2400 D850 D385 counter
Add 50mm to depth for air gap brackets			
<b>Internal (mm):</b>	H600 W390 D490	H600 W390 D490	H600 W390 D490
<b>Door Opening (mm):</b>	D1210	D1210	D1210
<b>Packed:</b>	H1200 W1510 D900	H1200 W2010 D900	H1200 W2475 D900
<b>Weight:</b> Add 5kg per product for packing	230Kg	306Kg	383Kg



### Important Information

	CPC3	CPC4	CPC5
<b>Capacity:</b> 1/3 pans/litres	7 / 320	10 / 420	12 / 540
<b>Construction:</b> Exterior Worktop/Pangrid Interior Door	0.7mm 430 stainless steel 1.2mm 430 stainless steel 0.6mm 304 stainless steel 0.7 430 ext / 0.7 304 int	0.7mm 430 stainless steel 1.2mm 430 stainless steel 0.6mm 304 stainless steel 0.7 430 ext / 0.7 304 int	0.7mm 430 stainless steel 1.2mm 430 stainless steel 0.6mm 304 stainless steel 0.7 430 ext / 0.7 304 int
<b>Power Supply:</b>	220V/240V 50Hz/1Ph 13 amp plug	220V/240V 50Hz/1Ph 13 amp plug	220V/240V 50Hz/1Ph 13 amp plug
<b>Power Input:</b> Start Up Running Compressor HP	26 amps 6.7 amps 3/4	26 amps 6.9 amps 1	29.7 amps 7.9 amps 1
<b>Energy Consumption:</b>	7.9kW in 24h	8.2kW in h	9.2kW in h
<b>Heat Rejection:</b> (Evaporating at -10°C in 32°C ambient)	1660 watts	1660 watts	2106 watts
<b>Refrigerant:</b>	R134a	R134a	R134a
<b>Refrigeration:</b>	Forced air refrigeration system with 1°C moving air curtain	Forced air refrigeration system with 1°C moving air curtain	Forced air refrigeration system with 1°C moving air curtain
<b>Defrost:</b>	Automatic off cycle	Automatic off cycle	Automatic off cycle
<b>Insulation (max):</b> ODP Zero Polyurethane	75mm	75mm	75mm
<b>Noise Output:</b>	dBA	dBA	dBA
<b>Fittings:</b> Shelves 1/3GN Pans(not included)	6 x 1/1GN (W325xD530) 7	8 x 1/1GN (W325xD530) 10	10 x 1/1GN (W325xD530) 12

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams are committed to a policy continuing product development and innovation and as such, we reserve the right to change product specifications stated without prior notice.



V12006 – JW/5/06



**Aishwarya Consolidates Pvt. Ltd.,**  
 #19, Frist Floor, 10<sup>th</sup> 'B' Main, 27<sup>th</sup> Cross,  
 Third Block Jayanagar, BANGALORE – 560 011, INDIA  
 Tel: +91-80-2664 1200/1/2 Fax: +91-80-2664 1204  
 E-mail : [aishtek@vsnl.com](mailto:aishtek@vsnl.com) [www.aishwaryaconsolidates.com](http://www.aishwaryaconsolidates.com)