



**Model: *Mobile Banqueting Trolley*
MRC16SS & MHC16SS**

Project:

Location:

Item #:

Quantity:

Variant	Op Temp & Storage
MRC16SS	+1/+4°C - General Produce
MHC16SS	+78/+82°C - General Produce

Key Features

- Tough, durable stainless steel exterior and interior
- Designed to transport large quantities of cold/hot food from the kitchen to the serving/banqueting area with built-in all round bumper strip for added protection
- All cabinets equipped with 16 pairs of tray slides to accommodate 1/1 or 2/1 GN pans
- Heating and refrigeration systems ensure hot and cold food remains in first class condition with minimal dehydration
- Easy to clean, hygienic stainless steel base with radius corner and removable stainless steel tray slides and support racking
- Self-closing lockable doors with 90° opening, fitted with easy to clean and replace magnetic balloon gaskets
- Heavy duty swivel and brake castors for easy positioning and mobility
- 75mm environmentally friendly ODP Zero (Ozone Depletion Potential) foam insulation for excellent thermal efficiency and performance
- HACCP compliant



MRC16SS



MHC16SS

	MRC16SS	MHC16SS
External (mm):	H2000 W807 D885	H1768 W807 D885
Internal (mm): (width per section)	H1235 W587 D652	H1307 W587 D652
Packed (max):	H2000 W890 D820	H1780 W890 D820
Weight: Add 5kg per product for packing	143kg	133kg

Important Information

	MRC16SS	MHC16SS
Capacity:	16 x 2/1GN or 32 x 1/1 GN (D50mm) 594L	16 x 2/1GN or 32 x 1/1 GN (D50mm) 495L
Construction: Exterior Interior Door	0.7mm 304 0.6mm 304 stainless steel 0.7 mm 304 ext / 0.6 mm 304 stainless steel	0.7mm 304 0.6mm 304 stainless steel 0.7 mm 304 ext / 0.6 mm 304 stainless steel
Power Supply:	220V/240V 50Hz/1Ph 13 amp plug	220V/240V 50Hz/1Ph 16 amp plug
Power Input: Start Up Running Compressor HP	12 amps 3.0 amps 1/4	12 amps 2.5 amps 1.3 KW * 3 Heater
Heat Rejection:	507 watts	665 watts
Refrigerant::	R134a	N/A
Defrost:	Automatic off-cycle	N/A
Insulation (max): ODP Zero Polyurethane	75mm	75mm
Fittings: Shelves Trayslides	32 x 2/1GN (W530xD650) 16 pairs	32 x 2/1GN (W530xD650) 16 pairs

All refrigeration equipment require adequate ventilation for efficient and effective performance.

Williams are committed to a policy continuing product development and innovation and as such, we reserve the right to change product specifications stated without prior notice.



V12008 JW/07/06

Aishwarya Consolidates Pvt. Ltd.,
 #19, Frist Floor, 10th 'B' Main, 27th Cross,
 Third Block Jayanagar, BANGALORE – 560 011, INDIA
 Tel: +91-80-2664 1200/1/2 Fax: +91-80-2664 1204
 E-mail : aishtek@vsnl.com www.aishwaryaconsolidates.com