



Model: Roll-in Modular Ruby *RMR1T & RMR2T*

Project:

Location:

Item #:

Quantity:

<i>Variant</i>	<i>Op Temp & Storage</i>
HRMR1T	+1/+4°C - General Produce
MRMR1T	-2/+2°C - Meat Storage
LRMR1T	-18/-22°C – Frozen Food
HRMR2T	+1/+4°C - General Produce
MRMR2T	-2/+2°C - Meat Storage
LRMR2T	-18/-22°C – Frozen Food

Optional Features

- Glass doors (not available for L model)
- Roll through door
- 15mm / 90mm Insulated floor
- Internal light

Key Features

- Modular construction facilitated installation in areas with restricted access
- Tough stainless steel exterior and interior for easy cleaning and durability
- Accommodates 1/1 & 2/1 Gastronorm or Euronorm trolleys
- Digital temperature controller with built-in alarm and fail safe run facility
- Self-closing lockable half doors with 90° opening, fitted with easy to clean and replace magnetic balloon gasket
- Environmentally friendly ODP Zero (Ozone Depletion Potential) foam insulation for excellent thermal efficiency and performance
- Top mounted pod refrigeration system for easy servicing and maintenance
- Automatic electric defrost and vaporizer system
- Design for efficient and effective operation in 32°C ambient environments
- HACCP compliant



Dimensions

	HRMR1T	MRMR1T	LRMR1T	HRMR2T	MRMR2T	LRMR2T
External (mm):	H2460 W905 D982	H2460 W905 D982	H2460 W905 D982	H2460 W1850 D982	H2460 W1850 D982	H2460 W1850 D982
Internal (mm): (width per section)	H1843 W715 D830	H1843 W715 D830	H1843 W715 D830	H1863 W760 D830	H1863 W760 D830	H1863 W760 D830
Door Opening (mm):	D1776	D1776	D1776	D1776	D1776	D1776
Wood Packed (max):	H2700 W980 D1060	H2700 W980 D1060	H2700 W980 D1060	H2700 W1940 D1060	H2700 W1940 D1060	H2700 W1940 D1060
Weight: Add 5kg per product for packing	190kg	190kg	190kg			

Important Information

	HRMR1T	MRMR1T	LRMR1T	HRMR2T	MRMR2T	LRMR2T
Capacity: cu.ft/litres/GN Trolley	43.7 /1238/1 GN Trolley	43.7 /1238/1 GN Trolley	43.7 /1238/1 GN Trolley	98.8 / 2800/2 GN Trolley	98.8 / 2800/2 GN Trolley	98.8 / 2800/2 GN Trolley
Construction: Exterior Interior Door	0.7mm 430 0.6mm 304 stainless steel 0.8 mm 430 ext / 0.6 mm 304 stainless steel	0.7mm 430 0.6mm 304 stainless steel 0.8 mm 430 ext / 0.6 mm 304 stainless steel	0.7mm 430 0.6mm 304 stainless steel 0.8 mm 430 ext / 0.6 mm 304 stainless steel	0.7mm 430 0.6mm 304 stainless steel 0.8 mm 430 ext / 0.6 mm 304 stainless steel	0.7mm 430 0.6mm 304 stainless steel 0.8 mm 430 ext / 0.6 mm 304 stainless steel	0.7mm 430 0.6mm 304 stainless steel 0.8 mm 430 ext / 0.6 mm 304 stainless steel
Power Supply:	220V/240V 50Hz/1Ph 13 amp plug	220V/240V 50Hz/1Ph 13 amp plug	220V/240V 50Hz/1Ph 13 amp plug	220V/240V 50Hz/1Ph 13 amp plug	220V/240V 50Hz/1Ph 13 amp plug	220V/240V 50Hz/1Ph 13 amp plug
Power Input: Start Up Running Compressor HP	12 amps 2.5 amps 1/2	12 amps 2.5 amps 1/2	24 amps 4.2 amps 1	17 amps 3.5 amps 3/4	17 amps 3.5 amps 3/4	24 amps 4.3 amps 1.5
Heat Rejection: (Evaporating at -10°C in 32°C ambient)	507 watts	665 watts	1223 watts	665 watts	665 watts	1223 watts
Refrigerant::	R134a	R134a	R404a	R134a	R134a	R404a
Defrost:	Automatic off-cycle	Automatic electric Door mullion heaters	Automatic electric Door mullion heaters	Automatic off-cycle	Automatic electric Door mullion heaters	Automatic electric Door mullion heaters
Insulation (max): ODP Zero Polyurethane	90mm	90mm	90mm	90mm	90mm	90mm

All refrigeration equipment require adequate ventilation for efficient and effective performance.

Williams are committed to a policy continuing product development and innovation and as such, we reserve the right to change product specifications stated without prior notice.



V12008 JW/07/06

Aishwarya Consolidates Pvt. Ltd.,
 #19, Frist Floor, 10th 'B' Main, 27th Cross,
 Third Block Jayanagar, BANGALORE – 560 011, INDIA
 Tel: +91-80-2664 1200/1/2 Fax: +91-80-2664 1204
 E-mail : aishtek@vsnl.com www.aishwaryaconsolidates.com